

We claim:

1. An oven door locking mechanism which locks and unlocks the oven door at substantially different temperatures.

2. The oven door locking mechanism of claim 1 which locks the oven door at a temperature substantially higher than that at which it unlocks the oven door.

3. The oven door locking mechanism of claim 1 comprising a thermally responsive element capable of actuating locked and unlocked states of the oven door at different temperatures.

4. The oven door locking mechanism of claim 1 comprising a clutch mechanism.

5. The oven door locking mechanism of claim 4 wherein said clutch mechanism comprises:

a thermally responsive element;

a clutch; and

a lock member.

6. The oven door locking mechanism of claim 5 wherein said clutch has a first side and a second side, wherein said first side is engaged with said second side.

Sub A2J
7. The oven door locking mechanism of claim 5 further comprising:

5 a first spring in contact with said lock member, wherein said lock member defines a first side of said clutch as a keyed aperture, said keyed aperture is engaged with said thermally responsive element.

8. The oven door locking mechanism of claim 7, wherein the keyed aperture comprises an annular recess.

9. The oven door locking mechanism of claim 7 wherein said lock member has a first end and a second end, said first end defines said keyed aperture.

10. The oven door locking mechanism of claim 7 wherein said thermally responsive element defines a second side of said clutch as a slot, said slot in engagement with said keyed aperture.

11. The oven door locking mechanism of claim 7 wherein said first spring encompasses said lock member.

12. The oven door locking mechanism of claim 10 wherein said slot is elongated.

13. The oven door locking mechanism of claim 7 further comprising:

a latch mechanism defining a lock hole adapted to receive said lock member; and

a mounting bracket wherein said first spring is affixed to said mounting bracket.

14. The oven door locking mechanism of claim 10 wherein said thermally responsive element is a bimetallic leaf secured at a first end

16. ~~The oven door locking mechanism of claim 15 wherein~~
said receiver member is a bushing.

16. The oven door locking mechanism of claim 15 wherein
said receiver member is a bushing.

17. ~~An oven door locking mechanism comprising:~~

~~a clutch;~~

~~a thermally responsive element defining a second side
of said clutch as a slot;~~

~~a lock member defining a first side of said clutch as a
recess, said recess is engaged with said slot;~~

~~a latch mechanism defining a lock hole adapted to
receive said lock member at end opposite said recess, said lock hole comprises
a bushing; and~~

~~a mounting bracket comprising a first spring, said first
spring encompasses said lock member.~~

18. An oven door locking mechanism comprising:

a clutch;

a first bimetallic leaf adapted to deflect in response to heating and cooling and defining one side of said clutch as a slot;

5 a lock member defining a second side of said clutch as a recess, wherein said recess is engaged with said slot;

a latch mechanism defining a lock hole adapted to receive said lock member at end opposite said recess;

10 a second bimetallic leaf adapted to deflect into engagement with a second notch defined in said latch mechanism to selectively prevent actuation of said latch mechanism; and

a mounting bracket comprising a first spring, said first spring encompasses said lock member

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

Old A3